



STS-S60

Surface Mounted Speaker and Microphone



CONTACTA WINDOW INTERCOM SYSTEMS

Our customer side, free-standing speaker and omni-directional microphone modules is for use where one to one communication takes place at a counter or booth with a security screen.

Physical Data

Dimensions	Height – 2.95" Width – 2.36" Depth – 4.33"
Weight	1.21 lbs
Construction	Mild Steel
Finish Options	Powder Coated: Grey Leatherette or Black

Technical Data

Speaker

RMS	5W
Impedance	4 Ohms
Output	SPL 1W @ 1M 85dB
Frequency Response	150 Hz to 10,300 Hz

Microphone

Directional Response	Omni-Directional
Sensitivity	-42.5 +/- 2.0dB @ 1KHz (0dB=1V/pa)
Impedance	2K Ohms +/- @ 1KHz
Frequency Response	100Hz-5000Hz



Features

- › Semi-rigid goose neck microphone
- › Mute switch to isolate customer microphone input
- › Freestanding unit allows the staff to select the appropriate positioning on the counter

Applications:

For use where one to one communication takes place

- › Banks
- › Post offices
- › Information Centers
- › Airports
- › Ticket Counters

contacta 

Phone: (616) 392-3400
Email: sales@contactainc.com
www.contactainc.com