

STS-SU1

Staff Loudspeaker Unit



CONTACTA WINDOW INTERCOM SYSTEMS

The STS-SU1G Staff Microphone and Speaker Unit is part of the following Window Intercom System Models: STS-K001, STS-K002, STS-K003, STS-KJ020, STS-K035, STS-K058, and STS-K060.

Physical Data

Dimensions	Height – 2.61" (of base) 14.50" (fully extended) Width – 3.80" Depth – 6.02"
Weight	1.79lbs
Construction	Mild Steel
Finish Options	Powder Coated: Grey Leatherette or Black

Technical Data

Speaker

RMS	5W
Impedance	4 Ohms
Output	SPL 1W @ 1M 85dB
Frequency Response	150 Hz to 10,300 Hz

Microphone

Directional Response	Cardioid
Sensitivity	49.5dB+ 2dB @ 1kHz (0dB=1V/pa)
Impedance	1.6K Ohms+3-% @ 1k Hz
Frequency Response	150Hz - 10,500Hz



Features

- › Semi-rigid goose neck microphone
- › Mute switch to isolate customer microphone input
- › Freestanding unit allows the staff to select the appropriate positioning on the counter

Applications:

For use where one to one communication takes place

- › Banks
- › Post offices
- › Theaters
- › Information Centers
- › Public Transit Systems
- › Ticket Counters
- › Embassies
- › Government Buildings

contacta 

Phone: (616) 392-3400
Email: sales@contactainc.com
www.contactainc.com