

STS-SU1-3W

Staff Loudspeaker Unit with Dual Mute Switch



CONTACTA WINDOW INTERCOM SYSTEMS

The STS-SU1-3W Staff Microphone and Speaker Unit is a freestanding speaker and directional microphone with a semi-rigid stem, adjustable neck and dual mute switch.

Physical Data

Dimensions	Height – 2.76" (of base) 14.50" (fully extended) Width – 3.80" Depth – 6.02"
Weight	1.80lbs
Construction	Mild Steel
Finish Options	Grey Leatherette (STS-SU1-3W-G) or Black Textured Powder Coated (STS-SU1-3W-B)

Technical Data

Speaker

RMS	5W
Impedance	4 Ohms
Output	SPL 1W @ 1M 85dB
Frequency Response	150 Hz to 10,300 Hz

Microphone

Directional Response	Cardioid
Sensitivity	49.5dB+ 2dB @ 1kHz (0dB=1V/pa)
Impedance	1.6K Ohms+3-% @ 1k Hz
Frequency Response	150Hz - 10,500Hz

Features

- The dual mute switch provides the following options:
- › Mute of the staff microphone only
 - › Mute of both the staff and customer side microphones
 - › Open microphones for both the staff and customer

Applications:

For use where one to one communication takes place

- › Banks
- › Information Centers
- › Public Transit Systems
- › Ticket Counters
- › Government Buildings

contacta 

Phone: (616) 392-3400
Email: sales@contactainc.com
www.contactainc.com