

# K009-IP

## IP55 Surface Mounted Call Unit



CONTACTA WINDOW INTERCOM SYSTEMS

The surface mounted call unit is designed for installation at head height. The call button on the front of the unit triggers an audible alert to inform staff of a customer's presence and open a handsfree conversation channel. It has an LED light to help users find the system when it is dark outside.

### Physical Data

Dimensions	Height – 7.2" Width – 4.8" Depth – 3.14" Cable length - 8.3ft
Construction	Mixed, Stainless Steel, Polycarbonate
Finish	Black Powder Coated Leatherette

### Technical Data

Speaker	Rated Power Input	15W
	Impedance	4 Ohm
	Sensitivity	SPL 1W @ 1M 84dB
	Frequency Response	100Hz - 20,000Hz
Microphone	Directional Response	Omnidirectional
	Frequency Response	100Hz - 20,000Hz
	Sensitivity	-42dB +/1 3dB @ 1kHz (0dB=1V/pa)
	Output Impedance	2.2K



### Applications

For use outdoors where one to one communication takes place through screen barrier:

- › Outdoor access points (gates, security doors, etc.)
- › Transport and distribution depots
- › Ports and ferry terminals
- › Car parks/parking lots
- › Medical, healthcare, and mass testing facilities
- › Drive through services (food and beverage, retail, banking)

### Standards

- › BS EN 60118-4 in correct installations
- › CE, ROHS and WEE compliant
- › K009-IP - Ingress protection rated IP55 against penetration from water and dust.

 **contacta**

Phone: (616) 392-3400  
Email: sales@contactainc.com  
www.contactainc.com