



Portable Loop

Mobile Hearing Loop System



Item Codes:

PIL

PIL-M73

PIL-M300

Applications

- › Pharmacy Counters
- › Small Meetings
- › Libraries
- › Banks
- › Healthcare Settings
- › Workplace
- › Portable Personal Use
- › Information Centers

CONTACTA ONE -TO-ONE LOOP SYSTEMS

The Contacta Portable Loop is a compact, mobile desktop hearing loop system designed to provide clear, accessible communication in a variety of settings. Its portable design allows the unit to be easily moved between rooms and locations as needed, making it a flexible solution for one-to-one conversations and smaller meeting spaces.

It features an integrated microphone, amplifier, hearing loop aerial, and rechargeable battery, providing a complete hearing loop solution in a single, convenient unit. For environments with moderate to high ambient noise, an external microphone can be connected to the rear of the Portable Loop via a 3.5mm jack to help improve speech clarity and communication.

Ideal for situations where flexible accessibility is needed, the Portable Loop makes it easy to provide hearing loop support wherever it is required.

Features

- › Advanced audio processing features Automatic Gain Control (AGC), compression, and noise gate
- › Constant-current loop drive
- › LED indicator shows loop drive and battery and charge status
- › Magnetic field strength distance to approximately 24"

contacta

Phone: (616) 392-3400
Email: sales@contactainc.com
www.contactainc.com

Physical Data

Dimensions	Height – 9.84" Width – 10.82" Depth – 4.33"
Weight	1.76lbs
Construction/ Finish	Black ABS Plastic

Accessories

- › RX20 Loop Listener
- › RX30 Rechargeable Loop Listener
- › MIC-M73 Microphone
- › MIC-M300 Microphone

Standards

- › CE, ROHS and WEEE compliant
- › BS EN 60118-4, in correct installations

Technical Data

Internal Battery	NiMH battery pack	Battery life approximately 4 hours
PSU	Power supply	18 VDC
Microphone	-	Electret capsule
Power and Status	Power and status LED Indication	Green/red LED
Protection	-	Self-resetting polyfuses, multiple on chip thermal shutdown
External Audio In	Connection	Boundary microphone or SCART Lead
DC Power	Connection	.21cm DC jack